

# FORMULA 65 DEEP AT OPTICOM





Adhesive Left/Right/Down - 19044



Double Sided Screen with Down Arrow - 19043



Formula 65 Deep Opticom



Recessed Box -- Frames F65 Extreme - 19040



Wall Bracket - 19045 -- Double Sided Screen with Left/Right Arrows - 19042

Device for emergency lighting that is highly flexible in use. The symmetry and the great uniformity of its illumination means that Formula 65 LED Deep Opticom can be installed without a pre-fixed positioning, to the walls, ceiling, suspended or recessed. The white polycarbonate body houses a double-reflective optic that in turn integrates two highly efficient LED series (greater than 160 lumen/Watt). The high transparent polycarbonate diffuser was designed to seal in the optic group so that the device offers a ip65 protection level. The external shell features a number of pre scored access points for direct fitting on all the most common junction or flush-mounted boxes. The standard autonomy of 1h can be extended to 1.5h, 2h, 3h or 8h using the Opticom Technology app to automatically change the outgoing luminous flux. The device is designed to accommodate the feed-through cabling (section 2.5mm) and is suitable for use with the M20 commercial cable brackets, both for smooth and corrugated tubes of 16 and 20mm diameter.

Product category: Luminaires, Exit Signs

## ACCESSORIES SUPPLIED

Order Code	Description
	No 2 Cable Gland M20
	Adapter Tube 16/20 White
19044	Adhesive Left/Right/Down F65

## TO BE ORDERED SEPARATELY

Order Code	Description
19040	Recessed Box + Frame F65
19041	Ceiling Bracket F65
19042	Double Sided Screen with Left/Right Arrows F65
19043	Double sided Screen with Down Arrows F65
19045	Wall Bracket Suspended F65
15036	LG Module
15037	LGFM Module
15038	DALI Module

## CONTROL SYSTEM ORDER CODES

### OPTICOM

Part No.	Net Weight	Insulation Class	Emergency Operation Mode	Battery	Battery Duration	Luminaire Power	Luminaire Flux	Luminaire Flux in Emergency	Autoripara Battery
19217	0.7kg	II	Non-maintained mode	LTO 4.8V 1.2Ah	-	7.5W	-	250/85lm	-
19218	0.7kg	II	Non-maintained mode	LTO 2 X 4.8V 1.2Ah	-	7.5W	-	550/190lm	-
19219	0.7kg	II	Maintained mode	LTO 4.8V 1.2Ah	-	7.5W	130lm	315/110lm	-
19252	0.7kg	II	Non-maintained mode	LTO 4.8V 1.2Ah	-	7.5W	-	315/110lm	-

This product is currently unavailable.