

LITE SEF LED



Save Energy Flood (SEF) LED is an outdoor floodlight with a body made of aluminium and a polished diffusing reflector.

The screen is made of tempered high transparency glass and the junction box allows the wiring of the fixture without disassembling the light source compartment.

This grants a fast and safe installation without endangering the protection degree of the fixture.

SEF LED is also available with integrated movement and twilight sensor.

Product category: Floodlights, Outdoor

FEATURES

Application	Courtyards, Driveways and Paths
Ballast	For constant current LED
Colours (RAL)	Black, White
IK Rating	IK08
IP Rating	IP65
Material	Die-cast Aluminium
Norms	[52,84,97,100,100]
Optics	Rotosymmetrical
Voltage (v)	230v

CONTROL SYSTEM ORDER CODES

TRADITIONAL

Part Number	Net Weight (kg)	Insulation Class	Temperature (K)	Luminaire Power (W)	Luminaire Flux (lm)	Luminous Efficacy (lm/W)
86130	0.3kg	I	4000K	10W	900lm	91lm/W
86131	0.4kg	I	4000K	20W	1800lm	91lm/W
86132	0.6kg	I	4000K	30W	2700lm	91lm/W
86133	0.9kg	I	4000K	50W	4500lm	91lm/W
86134	1.6kg	I	4000K	100W	9000lm	91lm/W
86135	5kg	I	4000K	200W	18000lm	91lm/W
86136	6.8kg	I	4000K	300W	27000lm	91lm/W
86137	0.3kg	I	4000K	10W	900lm	91lm/W
86138	0.4kg	I	4000K	20W	1800lm	91lm/W
86139	0.6kg	I	4000K	30W	2700lm	91lm/W
86140	0.9kg	I	4000K	50W	4500lm	91lm/W
86141	1.6kg	I	4000K	100W	9000lm	91lm/W
86142	5kg	I	4000K	200W	18000lm	91lm/W
86143	6.8kg	I	4000K	300W	27000lm	91lm/W