

SAVING LED



Lighting fixture designed for undercabinet and indirect illumination, both for professional use in shopping malls, shop windows and for domestic use.

The use of high-efficiency LEDs grants very low overall consumption.

Available in five different sizes, the fixture is equipped with integrated through wiring for continuous row installation which results in an even light beam free from black areas between one fixture and the other.

No special accessories are needed for the continuous row installation, which is rigid when done head to head between the luminaries or flexible when done with the power wire provided in the packaging.

The battens, according to the type, can be equipped with or without an onboard switch that acts only on its fixture even when installed in a continuous row.

Product category: Indoor, Outdoor, Industrial, Waterproof

FEATURES

Application	Offices, Production, Warehouses
Ballast	For constant current LED
Colours (RAL)	Grey RAL 7035
IK Rating	IK05
IP Rating	IP65
Material	Self-extinguishing Thermoplastic (Polycarbonate)
Norms	[45,77,95,98,100]
Optics	Symmetrical diffusing
Voltage (v)	230v

ACCESSORIES SUPPLIED

Order Code	Description
	Hose Press M20

TO BE ORDERED SEPARATELY

Order Code	Description
19367	INV P&L LED SE/SA 1h 60-180v

CONTROL SYSTEM ORDER CODES

TRADITIONAL

Part Number	Net Weight (kg)	Insulation Class	Temperature (K)	Luminaire Power (W)	Luminaire Flux (lm)	Luminous Efficacy (lm/W)
72010	2kg	I	4000K	34W	4400lm	130lm/W
72011	2kg	I	4000K	50W	6400lm	129lm/W
72012	2kg	I	6500K	34W	4400lm	130lm/W
72013	2kg	I	6500K	50W	6400lm	129lm/W