

## FH-M



Available in Smart Driver Auto-dimmable version, controllable from the Central Unit, or with an RD system that has a selector to set 4 steps of luminous flux.

Product category: Surface, Suspended, Floodlights, Ceiling Mounted, Indoor, Outdoor, Industrial

## FEATURES

<b>Application</b>	Industrial
<b>Colour Rendering</b>	>80
<b>Colour Rendering</b>	RAL 7040
<b>Colour Temp. (K)</b>	4000K
<b>IK Rating</b>	IK09
<b>IP Rating</b>	IP66
<b>Material</b>	Polyester powder-coated diecast aluminium
<b>Norms</b>	EN 60598-1, EN 60598-2-1, EN 60598-2-22, DIN 18031-3, EN 62471 (photobiological risk-free), 2014/53/EU
<b>Voltage (v)</b>	230v

## ACCESSORIES SUPPLIED

Order Code	Description
-	SD Radio / 1-10V Interface
-	Vandal-Proof Screws
-	M20 Cable Gland with Vent Valve
-	Goniometric Bracket
15039	Smart Dimmer Light Sensor

## TO BE ORDERED SEPARATELY

Order Code	Description
12659	Mounting Bracket for Electrified Bar
12661	Pole End Cap 2X 60-76
12663	High Bay Light Suspension Cable
12657	Protective Grid

This product is currently unavailable.